

ADVR7016T-LM 1 SATA 16ch Analog HD DVR



Features:

- Support ADH-M series front-end real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7016T-LM

Interface:

Parameter:

	Model	ADVR7016T-LM
System	Main processor	Hi 3531
	video codec	H.264
Video	Encode	16*1080N@15fps/16*AHD-M
	Decode	1*1080N@15fps/1*AHD-M
	Multi-mode input	Pure Analog: 16*1080N; 16*AHD-M; 8*AHD-M;16*AHD-L; Mixed: 4*AHD-M(Analog)+4*720P(Network); 8*AHD-M (Analog) +8*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20* 960H
	Audio compression	G.711A
Audio	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Recording and Playback	Playback Channels	4 (pure local input mode)
	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
Storage and backup	Backup mode	Network backup、USB HDD, USB writer、SATA writer
	Video input	16 BNC
Interface	Video output	1ch VGA,1ch HDMI
	Audio input	2ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 6T)
	Wireless	3G、WIFI(expand via USB)
	Other	Power
dimension		255mm(length)* 236mm(width)* 44mm(height)