




























SLIKA	MODEL	OPIS	CENA
KOLOR MONITORI			
	DT433/D4	1. 4.3" kolor TFT monitor bez slušalice 2. Tasteri osetljivi na dodir 3. Podržava 12 različitih melodija 4. Dimenzije: 168*106*17mm	55,00
	DT437/D4	1. 4.3" kolor TFT monitor 2. Tasteri osetljivi na dodir 3. Podržava 12 različitih melodija 4. Dimenzije: 191*186*37mm	65,00
	DT47MG crni/beli	1. 7" kolor TFT monitor osetljiv na dodir 2. Ugrađena memorija za beleženje propuštenih poseta 3. Podržava 12 različitih melodija 4. Dimenzije: 226*132*18mm	120,00
	DF4	Upgraded DF series 2easy monitor, glass surface wall mount, with a 4.3" 16:9 TFT screen 6 touch keys with mute, selects, talk, unlock and divert. Suitable for 2 wire system, Optical glass panel provides clear view of image, easy clearance and prevent discoloration.	45,00
	DF7	Upgraded DF series 2easy monitor, glass surface wall mount, with a 7" 16:9 TFT screen 6 touch keys with mute, selects, talk, unlock and divert. Suitable for 2 wire system, Optical glass panel provides clear view of image, easy clearance and prevent discoloration.	60,00
	DX482	<ul style="list-style-type: none"> • 1280*600 pixels TFT screen • Touch screen operation • Talk & Unlock touch sensor button • Status indicator • Color icon display • Multi languages • Visitor's video memory recording • Wi-Fi connectivity for call divert • IP camera compatibility(max.2K) • PIP&QUAD Image display • Call address set by menu input 	95,00
	DJ9	AUDIO SLUŠALICA HAND FREE, STAKLENA PLOČA	20,00
	DJ401	Dodatne audio slušalice za monitore DT471 i DT437	11,00
	DJ4	Audio slušalice individualne	40,00
POZIVNE TABLE SA KOLOR KAMEROM			
	DT610	Nazidna kolor kamera sa jednim pozivom	75,00
	DT610FE	Nazidna kolor kamera sa jednim pozivom, 170 stepeni ugao gledanja	95,00
	DT611/MK	Ugradna/Nazidna kolor kamera sa šifrnikom (nerđajući čelik)	120,00
	DT607/ID/S1	1. Nazidna kolor kamera, 170 stepeni ugao gledanja 2. Veliki displej za imena 3. Integrirana kontrola ulaska na priveske do 320 privezaka	120,00
	DT607/ID/S2		122,00

	DT607/ID/S3	3. Integrisana kontrola ulaska na privezke do 320 privezana 4. IP44 zaštita 5. Dimenzije:179*94*42mm	124,00
	DT607/ID/S4		126,00
	DMR18/ID	Digitalna kolor kamera sa kontrolom pristupa • Lista stanara na displeju • Integrisana kontrola ulaska (šifra/privezak) • Srpski meni	220,00
	DMR21/ID/S4	Ugradna kolor kamera sa 4 poziva i kontrolom pristupa, jedan red tastera	130,00
	DMR21/ID/D8	Ugradna kolor kamera sa 8 poziva i kontrolom pristupa, dva reda tastera	145,00
	EP21/S12	Proširenje od 12 tastera za pozivne table, jedan red tastera	68,00
MODULARNI SISTEMI			
	DT821/VD	Modul sa kamerom, 170° ugao gledanja	95,00
	DT821/AD	AUDIO MODUL ZA AUDIO INTERFONE DJ9	60,00
	DT821-T5	Integrated Module Multi function module 5 Inch TFT touch screen, Full glass surface, Access card with both 12.5Khz Password unlock Customizable menu	80,00
	DT821/TFT	Modul sa monitorom, prikazuje spisak stanara	74,00
	DT821/MK	Modul sa šifраторom za kontrolu ulaska	30,00
	DT821/DR	Modul sa ugrađenom kontrolom ulaska na privezak	55,00
	DT821/S4	Modul sa četiri tastera, tasteri na dodir	30,00
	DT821/M2	Modul sa 2 tastera, mehanički	26,00
	DT821/M3	Modul sa 3 tastera, mehanički	28,00
	DT821/M4	Modul sa 4 tastera, mehanički	30,00
	DT821/M8	Modul sa 8 tastera, mehanički	38,00

	DT821/S0	nerđajući čelik, zamena za taster	4,00
	DT821/LB	Info modul	18,00
	DT821F-2X1	Ugradna kutija za dva modula	20,00
	DT821F-3X1	Ugradna kutija za 3 modula	30,00
	DT821F-3X2	Ugradna kutija za 6 modula	50,00
	DT821S-3X1	Nazidna kutija za tri modula	38,00
	DT821S-2X2	Nazidna kutija za četiri modula	
	DT821S-3X2	Nazidna kutija za šest modula	60,00
IP VIDEO INTERFONI			
	IX471S	<ol style="list-style-type: none"> PoE power supply; 7 inch TFT screen (800*480); Touch screen operation; Full duplex communications; Support mult-languages menu (customization) ; Support 12 kinds of ring tones; 174mm*161mm*22mm <ol style="list-style-type: none"> Monitor, Talk, Unlock; Intercom call, Inner call, Guard unit call; Call divert to smart phone APP by SIP; Built-in memory function ; Onvif IP camera surveillance; Proximity card management; Password management; On-line firmware upgrade 	100,00
	IX470/TD7-W/B	<ol style="list-style-type: none"> PoE power supply 7"IPS TFT screen (1024 * 600) with all viewing direction Touch screen operation Slim and ultra flat design Super thin glass front panel Embedded Wi-Fi antenna for wireless connectivity Short cut setting & Favorite setting White and Black housing for chose Support both horizontal and vertical mounting 226mm*132mm*18mm 	120,00
	IX482-W	<ol style="list-style-type: none"> PoE power supply 7" TFT screen (1024 * 600) Touch screen operation Slim and ultra flat design Super thin glass front panel Embedded Wi-Fi antenna for wireless connectivity Short cut setting & Favorite setting 185mm*159mm*18.5mm 	120,00

	<p>GL471</p>	<p>Guard unit with handset 1.Camera View.could pair with an IP Camera as its' owncamera, when calling to other monitor, showing paired IP Camera's image. 2.Support desk mount, special for secure room or reception. 3.Transfer calls to APP when the devices is unattended.</p>	<p>110,00</p>
	<p>IX610</p>	<ol style="list-style-type: none"> 1. 720 Wide angle fisheye camera; 2. Aluminum front cover 3. Auto sensor night vision LED; 4. Big back-lit push buttons 5. Simple & compact deisgn; 7. PoE power supply; 8. IP 54 rate 160mm*60mm*31.5mm 	<p>110,00</p>
 	<p>IX-850 IX-850F</p>	<ol style="list-style-type: none"> 1. 720P Wide angle fisheye camera; 2. Stainless steel front panel; 3. 5-inch TFT monitor(800x480 pixels); 4. Touch screen operation(5mm tampered glass); 5. PoE power supply; 6. RFID Proximity card access control; 7. Password access control with touch keypad; 8. Auto sensor night vision LED; 9. Flush or surface mount optional; 10. IP 54 rate 328mm*136mm*48mm(Flush) 281mm*1110mm*44mm(Surface) <ol style="list-style-type: none"> 1. Name list/Room number call; 2. Multi language audio prompt; (customized) 3. Advanced installer passowrd control; 4, Public & private password for access control; 5. RF CARD management 	<p>240,00</p>
	<p>IX-RLC</p>	<p>IP RELEJNI MODUL ZA DRUGU BRAVU</p>	<p>60,00</p>
	<p>V CONTROL 3-F</p>	<p>Vcontrol 3-F Waterproof Fingerprint Video Intercom Access Intercom > 2.4G WiFi connection, > Android and iOS available > Full duplex voice intercom > 2MP+wide angle camera and night vision > Support TF card with unlimited capacity > Support motion detection, playback, take picture/video, unlock remotely</p> 	<p>130,00</p>
	<p>VCONTROL 4-F</p>	<p>WiFi Waterproof Fingerprint Video Intercom Access Intercom, > 2.4G WiFi connection, > Android and iOS available > Full duplex voice intercom > Support TF card with unlimited capacity, unlock remotely</p>	<p>75,00</p>
	<p>RS-SK480050</p>	<ol style="list-style-type: none"> 1. AC100-240V, 50/60Hz 2. Output: 48V0.5A 3. with EU plug AC Cable 	<p>10,00</p>
	<p>PoE switch-4P</p>	<ol style="list-style-type: none"> 1. Power-over-Ethernet (IEEE 802.3af Class 0) 2. 4 PoE outputs; 3.10 BASE-T / 100 BASE-TX Ethernet (RJ-45); 4, MAX 32W for each PoE port; 	<p>40,00</p>

	RS-DS0802A-V5C	8+2G PoE Switch Built-in power supply standard full hundred megabytes 135w	65,00
	RS-DS0802A-V2	8+2G PoE Switch Built-in power supply standard uplink gigabit 135w	80,00
	RS-DS1602A-T6	16+2G PoE Switch Built-in power supply standard uplink gigabit 135w	150,00


DODATNA OPREMA ZA V-TECH VIDEOINTERFONE














	DT-DBC2S	Distributer za dve unutrašnje jedinice	11,00
	DT-DBC4S	Distributer za četiri unutrašnje jedinice	22,00
	DT-DBC4F	4-way outputs for multi IM,2 din rail	17,00
	DT-DBC4R	Distributer I pojačivač signala za četiri unutrašnje jedinice	28,00
	DT-BDU	Pojačivač signala na svakih 32 unutrašnje jedinice	64,00
	DT-IPG	Pojačivač signala na svakih 32 unutrašnje jedinice	65,00
	PC7	Power combo (include power seperator),24VDC 1.5A output,4 din rail	32,00
	PC7H	Power combo (include power seperator),24VDC 2.5A output,5 din rail	41,00
	PC9	Power combo (include power seperator),24VDC ?A output,?din rail	20,00
	DT-DPS	Power seperator,2 din rail	12,00
	DT-RLC	Modul za povezivanje svetla na interfonski sistem	14,00
	DT-TPS	Konverter za telefonsku liniju	61,00











CENE SU BEZ PDV-a




NOVO U PONUDI - VIDEO INTERFONI

SISTEM NA 2 ŽICE

	T-OS14E	7" Main Slim Outdoor Station (Touch Panel/Black) 7" touch panel outdoor station,0.3MP Camera, can be powered up by system power supply or independent one, CCTV surveillance by built-in interface, customized GUI design for name label and virtual keyboard,volume adjustable2 locks mangement, 3 devices max in the same system. Slim aluminium panel with 365*125*8mm	290,00
--	----------------	---	---------------

	T-OS17	Mini Outdoor Station, 2-button(Surface mounted) CMOS camera with 600TVL, visual angle 90°,aluminium front cover,auto fill-in LED light,1 call button, built-in IC card reader, 2 locks management,adjustable unlock time, IPX4 class	135,00
	T-OS01-IC	Mini Outdoor Station, 1-button CMOS camera with 0.3 mega pixel, visual angle 90°, white fill-in light, IC card, wall- mounted, aluminium faceplate SILVER	125,00
	T-OS08-B	Mini Outdoor Station, 2-button CMOS camera with 0.3 mega pixel, visual angle 90°, white fill-in light, IC card, wall- mounted, aluminium faceplate BLACK	125,00
	T-IS15	4.3" Indoor Monitor (Touch Key) Two wire indoor monitor with touch key, video intercom/monitor, max. 4 sets in 1 house, max. 128 sets in one system, ultra thin with 13.5mm, glass front panel	75,00
	T-IS07-W T-IS07-B	7" Indoor Monitor (Touch Panel/Black) Two wire indoor monitor with touch panel, resolution 800*480, TF Card: 2~32G (Class 10 preferred) video intercom/monitor, max. 4 sets in 1 house, max. 128 sets in one system.	120,00
	T-VD	Distributor for Indoor Monitor Supports max. 4 indoor monitors, for enhancing the video signal for monitors	24,00
	T-PS01-C	2 Wire Power Supply (Main) 1.5A Power supply, support 32 monitors, Working input voltage AC 90V~255V 50/60Hz, output voltage DC 30V, rated power 30W. This model is mainly for powering on outdoor staion, or for system monitors that less than 16pcs.	55,00
	T-PS02	2 Wire Extended Power Supply Working voltage AC100V~240V, output voltage DC 30V, for signal amplification, supports max.16 indoor monitors. This model is for powering on the monitors in the system	70,00
	IB-14E	7" Main Outdoor Station (Touch Panel) Installation Box Dimension: 340*144*50mm	13,00
IP SISTEMI			
	H-OS18-IC	8" Face Recognition Outdoor Station (2MP Camera) DC24V ONLY. Standard TCP/IP with face recognition function, resolution 800*1280, CMOS camera with 2 mega pixels, visual angle 123°, 8" TFT with advanced GUI, IC card, , door status detection, normal-close/open Dimension:130*308*26.50mm	540,00
	H-OS08-S-IC	4.3" Main Outdoor Station(1.3MP Camera) DC24V(support 24V POE power supply),Standard TCP/IP, resolution 480*272, CMOS camera with 1.3Mega Pixiels visual angle 110°, 4.3" TFT with advanced GUI, IC card, door status detection, normal-close /normal-open	380,00
	H-OS20S	Villa Outdoor Station (48V Grey) Standard TCP/IP, CMOS camera with 2 mega pixel, visual angle 78°, IC card, door status detection, name tag with LED backlight, unlock state timeout alarm, normal open/close, online update, surface mounted installation. Aluminium faceplate, 10000 user cards max.	135,00
	H-OS21S	Villa Outdoor Station (48V Grey) Standard TCP/IP, CMOS camera with 2 mega pixel, visual angle 78°, IC card, door status detection, name tag with LED backlight, unlock state timeout alarm, normal open/close, online update, surface mounted installation. Aluminium faceplate,10000 user cards max	140,00

	H-IS02S-W	4.3" Indoor Monitor (24V) DC 24V (support 24V POE power supply), Touch button controlling, standard TCP/IP, resolution 480*272, automatic photo capture, intercom function, advanced GUI. Black/White	80,00
	H-IS07S-W	7" Indoor Monitor (24V) DC 24V (support POE power supply), standard TCP/IP, resolution 800*480, automatic photo capture, intercom function, 8 defense zones, advanced GUI, text and photo information, home automation scenario functions. Black/White	140,00
	H-IS16S-W	7" Android Indoor Monitor (48V) DC 24V (support POE power supply), standard TCP/IP, resolution 1024*600, intercom function, 8 defense zones, smart home function integration, community calling service, user friendly GUI, WIFI	230,00
	H-IS32S-S	10.1" Indoor Monitor (24V) DC 24V (support 24V POE power supply), standard TCP/IP, resolution 1024*600, automatic photo capture, intercom function, 8 defense zones, SOS calling to guard station, receives text and photo information, elevator & IP camera management. Dimension: 247.5*165*17.40mm	295,00
	H-GU02	10.1" Android Guard Unit Standard TCP/IP, resolution: 1280*800, 10.1" capacitive touch screen 2MP CMOS Camera, VGA 640*480 MJPEG, connection up to 255 CCTV cameras, 5 melodies available, Call forwarding function, cards management, alarm and SOS information treatment, call to all system units,	
	IB-OS18S	Main Outdoor Station Surface Installation Bracket FOR H-OS18 Dimension:294.5*122.5*14mm	13,00
	IB-OS08F	Main Outdoor Station Flush mounting box FOR H-OS08 -S	13,00
	IB-OS20S	Villa Outdoor Station Rain Shield(H-OS20/ H-OS21) Dimension: 178*96*50mm	10,00
	TG1	IC Access Key Working Frequency: 13.56MHZ	10,00
	LG-AF-92N	48V Standard PoE Switch(11 PORTS) 9 ports with power, 2 port for uplink, power consumption 120W max, 220V AC/50Hz, data transmit via1,2/3,6 cable	80,00
SIP SISTEMI			
	SO801	8" SIP IP Face Recognition Outdoor Station (2MP) DC24V ONLY, 8" IPS display with resolution 800*1280, Dual 2MP COMS camera wide view angle, 9 unlock methods, with human proximity detection and auto fill-light, door status detection and tamper alarm, 2 lock management, compatible with cloud server mangement and LAN server mangement mode, support to save 20,000 faces locally, IC card, 3 different installation methods(Flush mounted, Surface mounted, fixing on column), built-in muti-languages, OTA online upgrade, elevator linkage, can be monitored by APP, IK07 Dimension:: 130*308*26.50mm Available color: Black	510,00
	SI701	7" SIP IP Indoor Monitor (48V) DC 24V (support standard 48V POE switch), 7" display with resolution 1024*600, intercom function, 8 defense zones, doorbell function available, RTSP for IP camera integration, resident list, black/ white list setting, voice message setting for visitor, smart home integration , built-in multi-language, WIFI connection for cloud intercom, compatible to 3rd party products. Dimension: 182*119*14.50mm Available color: Black	108,00

	<p>SIA01</p>	<p>10.1" SIP IP Android Guard Unit(48V) DC24V(support standard 48V POE switch), resolution: 1280*800, 10.1" capacitive touch screen, 2MP CMOS Camera, Address book for easy dialing, connection up to 255 cameras, 5 melodies available, Call forwarding function, cards management, wallpaper can be replaced easily, alarm and SOS information treatment, call to all system units, Dimension: 210*356*31.80mm Available colorL Black</p>	
	<p>LG-AF-92N</p>	<p>48V Standard PoE Switch(11 PORTS) 9 ports with power, 2 port for uplink, power consumption 120W max, 220V AC/50Hz, data transmit via 1,2/3,6 cable</p>	<p>80,00</p>
	<p>IB-OS14E</p>	<p>Main Outdoor Station Surface Installation Bracket FOR SO801 Dimension:294.5*122.5*14mm</p>	<p>13,00</p>