






























MODEL	KARAKTERISTIKE	CENA	
<b>DIGITALNI SNIMAČI</b>			
<p><b>XVR5104HS-X1</b></p>  <p><b>FULLHD 1080p</b></p> 	<p><b>Četvorokanalni</b> H.265+/H.265 pentabrid digitalni video snimač, podržava 4 HDCVI / TVI / AHD / analognih kamera do 5MP i dve dodatne IP kamere do 6MP H.265+/H.265/H.264+/H.264 kompresija, snimanje HDCVI/AHD/TVI kamera do rezolucije 5MP, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, podržava audio preko koaksijalnog kabla, brzina snimanja do 25fps u zavisnosti od rezolucija kamera (5M-N u 10fps, 4M-N i 1080p u 15fps, 1080N i niže u 25fps), 1 HDMI izlaz, 1 VGA izlaz, maksimalni kapacitet hard diska 6TB, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, napajanje 12VDC/2A</p>	85.00	
<p><b>XVR5108HS-X</b></p>  <p><b>FULLHD 1080p</b></p> 	<p><b>Osmokanalni</b> H.265 pentabrid digitalni video snimač, podržava 8 HDCVI/TVI/AHD/analognih kamera do 5MP i četiri dodatne IP kamere do 6MP H.265+/H.265/H.264+/H.264 kompresija, snimanje HDCVI/AHD/TVI kamera do rezolucije 5MP, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, podržava audio preko koaksijalnog kabla, brzina snimanja do 25fps u zavisnosti od rezolucija kamera (5M-N u 10fps, 4M-N i 1080p u 15fps, 1080N i niže u 25fps), 1 HDMI izlaz, 1 VGA izlaz, maksimalni kapacitet hard diska 10TB, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, napajanje 12VDC/2A</p>	120.00	
<p><b>XVR5116HS-X</b></p>  <p><b>FULLHD 1080p</b></p> 	<p><b>Šesnaestokanalni</b> Pentabrid digitalni video snimač za 16 kanala (HDCVI, analogni, TVI, AHD) + 8 IP kanala do 5MP Snimanje svih kanala do rezolucije 1920x1080px, 1080p@15fps, 720P@25fps, maksimalna brzina snimanja po kanalu 6 megabita, HDMI / VGA, 1 audio ulaz i izlaz, podržava 1 SATA HDD do 6TB, 2xUSB, RS485 port za povezivanje PTZ kamera, P2P opcija za lako umrežavanje, praćenje putem interneta: Web viewer, Smart PSS &amp; pametni telefoni</p>	180.00	
<b>KAMERE</b>			
	<p><b>HAC-HDW1239T-A-LED-0280B-S2</b></p>	<p>2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim, Full-color, Starlight. 0.001Lux/F1.6, 30IRE, 0Lux white Light on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. 130dB WDR. Domet LED dioda 40 metara. Integrisan mikrofoni. 12v napajanje. Odgovarajuća dozna je PFA130-E, PFA139</p>	57.00
	<p><b>HAC-HDW1200TL MQ-0280</b></p>	<p>2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.85, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E</p>	 36.00 

	<b>HAC-HDW1200TL MQ-A-0280</b>	2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.85, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E	 43.00 
	<b>HAC-HFW1200T-028B</b>	2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.9, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA134.	 34.00 
	<b>HDBW1200T-Z-2712-S5</b>	2MP HDCVI kamera u dome kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.7, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA137.	 65.00 
	<b>HFW1200R-Z-IRE6</b>	2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.8, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 60 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E.	 67.00 
	<b>PFA135</b>	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	8.00
	<b>PFA-134/137</b>	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	9.00
	<b>PFA130-E</b>	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	16.00
	<b>PFA13A-E</b>	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	9.00
	<b>HIB-810PTZ</b>	ČIP: Sony IMX323 + NVP2441, 4.5" Outdoor PTZ, 4 in 1 <b>REZOLUCIJA:</b> 2 Megapixel, <b>OSVETLJENJE:</b> 6pcs IR Array <b>OBJEKTIV:</b> 10X Zoom 5.1-51mm, PAL, default output CVI	217.00
	<b>HIB-918PTZ</b>	ČIP: Sony IMX323 + NVP2441, 7" High speed Outdoor PTZ, 4 in 1 <b>REZOLUCIJA:</b> 2 Megapixel, <b>OSVETLJENJE:</b> 8pcs Laser LED <b>OBJEKTIV:</b> 18X Zoom 5.35-96.3mm, PAL, default output CVI	 432.00
<b>CENE SU BEZ PDV-A</b>			