
























MODEL	KARAKTERISTIKE	CENA
DIGITALNI SNIMAČI		
<p>XVR5104HS-X1</p>  <p>FULLHD 1080p</p> 	<p>Četvorokanalni H.265+/H.265 pentabrid digitalni video snimač, podržava 4 HDCVI / TVI / AHD / analognih kamera do 5MP i dve dodatne IP kamere do 6MP H.265+/H.265/H.264+/H.264 kompresija, snimanje HDCVI/AHD/TVI kamera do rezolucije 5MP, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, podržava audio preko koaksijalnog kabla, brzina snimanja do 25fps u zavisnosti od rezolucija kamera (5M-N u 10fps, 4M-N i 1080p u 15fps, 1080N i niže u 25fps), 1 HDMI izlaz, 1 VGA izlaz, maksimalni kapacitet hard diska 6TB, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, napajanje 12VDC/2A</p>	95,00
<p>XVR5108HS-X</p>  <p>FULLHD 1080p</p> 	<p>Osmokanalni H.265 pentabrid digitalni video snimač, podržava 8 HDCVI/TVI/AHD/analognih kamera do 5MP i četiri dodatne IP kamere do 6MP H.265+/H.265/H.264+/H.264 kompresija, snimanje HDCVI/AHD/TVI kamera do rezolucije 5MP, 1 audio ulaz, 1 audio izlaz, dvosmerna audio komunikacija, podržava audio preko koaksijalnog kabla, brzina snimanja do 25fps u zavisnosti od rezolucija kamera (5M-N u 10fps, 4M-N i 1080p u 15fps, 1080N i niže u 25fps), 1 HDMI izlaz, 1 VGA izlaz, maksimalni kapacitet hard diska 10TB, 2 USB porta za bekap i kontrolu mišem, RS485 port za upravljanje PTZ kamerama, napajanje 12VDC/2A</p>	145,00
<p>XVR5116HS-X</p>  <p>FULLHD 1080p</p> 	<p>Šesnaestokanalni Pentabrid digitalni video snimač za 16 kanala (HDCVI, analogni, TVI, AHD) + 8 IP kanala do 5MP Snimanje svih kanala do rezolucije 1920x1080px, 1080p@15fps, 720P@25fps, maksimalna brzina snimanja po kanalu 6 megabita, HDMI / VGA, 1 audio ulaz i izlaz, podržava 1 SATA HDD do 6TB, 2xUSB, RS485 port za povezivanje PTZ kamera, P2P opcija za lako umrežavanje, praćenje putem interneta: Web viewer, Smart PSS & pametni telefoni</p>	230,00
KAMERE		
	<p>HDW1200M-0360-S4</p>	<p>2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.85, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA13A-E.</p> <p>FULLHD 1080p</p>
	<p>HAC-HDW1200EM-A-0280-S4</p>	<p>2MP HDCVI kamera u eyeball kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.85, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Fiksna optika 2.8mm. Nivo zaštite IP67. DWDR. Domet IC dioda 50 metara. Integrisan mikrofon. 12v napajanje. Odgovarajuća dozna je PFA130-E.</p> <p>FULLHD 1080p</p>

	HDBW1200T-Z-2712-S5	2MP HDCVI kamera u dome kućištu sa StarLight tehnologijom 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.7, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67, IK10. DWDR. Domet IC dioda 30 metara. 12v napajanje. Odgovarajuća dozna je PFA137.	 70,00 
	HFW1200R-Z-IRE6	2MP HDCVI kamera u bullet kućištu 4 u 1 TVI/AHD/CVI/CVBS režim. 0.02Lux/F1.8, 30IRE, 0Lux IR on. Maksimalna rezolucija 1920x1080. Varifokalna optika 2.7 - 12 mm. Nivo zaštite IP67. DWDR. Domet IC dioda 60 metara. 12v napajanje. Odgovarajuća dozna je PFA130-E.	 70,00 
	PFA135	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	8,00
	PFA137	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	10,00
	PFA13A-E	Nazidna dozna za sakrivanje kablova I konektora prilikom instalacije kamera	9,00
	HIB-810PTZ	ČIP: Sony IMX323 + NVP2441, 4.5" Outdoor PTZ, 4 in 1 REZOLUCIJA: 2 Megapixel, OSVETLJENJE: 6pcs IR Array OBJEKTIV: 10X Zoom 5.1-51mm, PAL, default output CVI	217,00
	HIB-918PTZ	ČIP: Sony IMX323 + NVP2441, 7" High speed Outdoor PTZ, 4 in 1 REZOLUCIJA: 2 Megapixel, OSVETLJENJE: 8pcs Laser LED OBJEKTIV: 18X Zoom 5.35-96.3mm, PAL, default output CVI	 432,00
VIDEONADZOR 5Mp CVI KOMELCO			
 KOMELCO	XVR-104P	Četvorokanalni 5MP Standard XVR support: 1 x HDD up to 4TB, 4ch Audio in / 1ch Audio out ; 1ch CVBS,1ch VGA,1ch HDMI, 3G & WIFI (The USB extension)	150,00
 KOMELCO	XVR-108P	Osmokanalni 5MP Standard XVR support: 1 x HDD up to 4TB, 4ch Audio in / 1ch Audio out ; 1ch CVBS,1ch VGA,1ch HDMI, 3G & WIFI (The USB extension)	230,00
	IRD-5010	ČIP: Sony Sensor IMX326 REZOLUCIJA: 5 Megapixel, OSVETLJENJE: 3pcs 3G LED OBJEKTIV: 2.8mm	50,00
	IRD-5020	ČIP: Sony Sensor IMX326 REZOLUCIJA: 5 Megapixel, OSVETLJENJE: 3pcs 3G LED OBJEKTIV: 2.8-12mm manual VF	68,00
	IRV-5020	ČIP: Sony Sensor IMX326 REZOLUCIJA: 5 Megapixel, OSVETLJENJE: 3pcs 3G LED OBJEKTIV: 2.8-12mm manual VF	88,00
CENE SU BEZ PDV-A			